



# TOWN

發公司  
富司

FOOD SERVICE EQUIPMENT CO., INC.

800/221.5032 718/388.5650 718/388.5860 customer.service@townfood.com www.townfood.com

Project \_\_\_\_\_

Item Number \_\_\_\_\_

Quantity \_\_\_\_\_



## Steamer Range and Cabinet with "AutoFill"

### Models

**YF-STMR-SS** is the 24" and 34" base models.

Natural or Propane fuel models are available.

Custom dim sum adaptor is available.

Custom designs for this unit are available.

### General

The Town YF-STMR is a gas fired four level steamer range. It is self contained and requires only gas and water connections. The unit features "AutoFill" which will automatically maintain the proper water level in the steam tank and ensures constant steam production. The unit is not thermostatically controlled. The primary usage is for cooking Asian foods, such as dumplings or dim sum. Foods such as whole fish or soup can be steamed in this unit. It can be used to cook any food that requires high, continuous heat from steam. Exterior of unit is constructed in 304 stainless steel. The steam generation tank is heavy duty stainless steel. The doors are double wall, insulated, complete with a positive latching mechanism. The interior fire chamber is constructed in stainless and is fully insulated by 1" thick fiber ceramic material. Unit is fired by a high power 32 tip jet burner (116 MBTUH). A pilot safety gas valve is provided. The unit can be customized with different body and cabinet sizes, as well as custom dim sum steamer plates.

### Standard Features

- listed by ETL to conform to ANSI Z83.11-2007
- listed by ETL to conform to ANSI/NSF4
- 2 door stainless steel steam cabinet with 4 shelves
- 4 perforated stainless steel trays to hold product for steaming
- stainless steel, positive lock latches
- "AutoFill" water tank with dump valve
- steam tank access from top of unit for easy cleaning/de-scaling
- single valve control with pilot safety device


### Options

- custom size steam cabinets
- custom size base unit
- dim sum steamer plates to replace cabinet
- drop or slide in base units
- pedestal mounted manual faucet faucet mounted on backsplash
- cabinet doors can be hinged left or right



Photo shown with left hinge.  
Comes standard with right hinge.

# STANDARD DIMENSIONS AND TECHNICAL DATA



## IMPORTANT

Commercial gas range(s) must be installed in accordance with state and local codes, or in the absence of local code with the NATIONAL FUEL GAS CODE- ANSI Z223.1. COMPLIANCE WITH ALL CODES IS THE RESPONSIBILITY OF THE OWNER AND THE INSTALLER.

COMMERCIAL GAS UNITS NEED ADEQUATE VENTILATION SYSTEMS. REFER TO *National Fire Protection Association Standard No. 96- "Vapor Removal from Cooking Equipment"*

CERTIFIED BY ETL TO CONFORM TO ANSI Z83.11- "GAS FOODSERVICE EQUIPMENT." Not intended for household use. For use by professionally trained personnel only.

CERTIFIED BY ETL/NSF TO NSF4/ANSI-4-COMMERCIAL COOKING, RETHERMALIZATION AND HOT FOOD EQUIPMENT-"SANITATION."

MINIMUM CLEARANCES- COMBUSTIBLE AND NON COMBUSTIBLE:  
Back Wall- 6" Left and Right Sides- 6" For use on non combustibile floors only.

**TOWN RESERVES THE RIGHT TO CHANGE DESIGN WITHOUT NOTIFICATION.**



# TOWN

發富公司

FOOD SERVICE EQUIPMENT CO., INC.

